Subject Index for
Telecommunications and Radio Engineering, Volume 48, 1993

Abbreviated sequential analysis: **10**, 46-50
Above-ground distance of propagation pattern: **11**, 47-54
Acoustic noise: **2**, 8-10
Acoustic-optic delay-line comb filters: **8**, 104-105
Acousto-optic spectrum analyzer: **6**, 128-130
Activity coefficient: **9**, 18-21
Adaptation: **1**, 6-10
Adaptive antenna arrays: **2**, 104-107
Adaptive filter: **7**, 89-96
Adaptive oscillator: **7**, 4-8
Adaptive spatial filtering algorithm: **12**, 69-73
Additive noise: **10**, 111-114
AFC of band-pass filters: **8**, 34-36
Airborne radar: **7**, 97-103
Airborne radar signal function: **11**, 55-60
Aircraft power unit: **9**, 61-66
Allocation: **11**, 29-34
Amplification of single-sideband signal components: **11**, 76-81
Amplifier stability: **2**, 137-139
Amplifier-parameter spread: **4**, 138-139
Amplifiers: **1**, 136-138
Amplitude and phase of emitted field: **8**, 100-103
Amplitude modulation: **9**, 76-79
Amplitude ratio criterion: **9**, 93-97
Amplitude spectrum: **4**, 70-74
Amplitude-phase distribution: **7**, 74-78
Amplitude-shift keyed signals: **5**, 126-128
Analog-digital converter: **3**, 121-123
Analog-to-code converters: **3**, 49-52
Analog-to-digit conversion of repetitive signals: **11**, 87-88
Analysis of operating modes: **8**, 113-115
Analytical and numerical estimates of power: **11**, 135-137
Angle-measuring systems: **12**, 121-125
Angular coordinate: **4**, 86-90
Angular motion with periodic *a posteriori* probability density : **12**, 109-113
Anomalous errors: **3**, 69-73
Antenna array: **2**, 72-75
Antenna optimization: **11**, 47-54
Antenna pattern-shaping circuit: **7**, 74-78
Antennas: **3**, 16-30; **7**, 67-73
Antipodal focusing: **2**, 92-95
Aperture field distribution: **9**, 129-134
Apparatus failure: **4**, 129-130
Approximation of ideal integrators: **8**, 26-33
Arbitrary scanning law: **7**, 79-82
Archimedes spiral: **6**, 112-115
Astatic PLL system: **12**, 25-30
Asymmetrical cyclically varying modulation indices: **11**, 109-113
Atmospheric precipitation: **5**, 99-102
Atmospheric turbulence: **11**, 41-46
Attenuation: **5**, 18-23, 26-27, 28-29
Attenuation factor: **5**, 24-25
Autocompensators: **5**, 95-98
Automatic control: **7**, 128-134
Automatic frequency control: **3**, 60-61
Automatic plate modulation: **7**, 9-13
Availability coefficient: **9**, 1-10

Balanced dipole antenna: **5**, 44-46
Band-pass vacuum-tube oscillators: **10**, 67-72
Bandgap: **1**, 11-17
Bandpass filter-transformer: **10**, 14-20
Barycentric method: **5**, 30-36; **6**, 107-111
Binary data transmission: **1**, 90-95
Bipolar transistor: **1**, 60-63; **4**, 126-128
Bipolar transistors: **10**, 91-95
Blast wave: **2**, 11-16
Boolean functions: **3**, 94-98
Boxer-Taylor method: **1**, 96-103
Bragg diffraction: **3**, 139-140
Broadband oscillators: **7**, 4-8
Broadband signals: **7**, 118-127
Broadcast networks: **11**, 1-6, 7-15
Buffer memory: **10**, 61-66
Bulk integrated circuits: **7**, 14-22
Butterworth, Chebyshev, and Zolotarev-Cower approximations: **8**, 123-131

Cable communications lines: **2**, 11-16
Calculation of error probability: **12**, 135-139
Calculation of parameters of FET devices: **11**, 141-144
Carrier frequency measurement: **5**, 69-74
Carrier recovery: **4**, 13-16

Subject Index for
Telecommunications and Radio Engineering, Volume 48, 1993

Abbreviated sequential analysis: **10**, 46-50
Above-ground distance of propagation pattern: **11**, 47-54
Acoustic noise: **2**, 8-10
Acoustic-optic delay-line comb filters: **8**, 104-105
Acousto-optic spectrum analyzer: **6**, 128-130
Activity coefficient: **9**, 18-21
Adaptation: **1**, 6-10
Adaptive antenna arrays: **2**, 104-107
Adaptive filter: **7**, 89-96
Adaptive oscillator: **7**, 4-8
Adaptive spatial filtering algorithm: **12**, 69-73
Additive noise: **10**, 111-114
AFC of band-pass filters: **8**, 34-36
Airborne radar: **7**, 97-103
Airborne radar signal function: **11**, 55-60
Aircraft power unit: **9**, 61-66
Allocation: **11**, 29-34
Amplification of single-sideband signal components: **11**, 76-81
Amplifier stability: **2**, 137-139
Amplifier-parameter spread: **4**, 138-139
Amplifiers: **1**, 136-138
Amplitude and phase of emitted field: **8**, 100-103
Amplitude modulation: **9**, 76-79
Amplitude ratio criterion: **9**, 93-97
Amplitude spectrum: **4**, 70-74
Amplitude-phase distribution: **7**, 74-78
Amplitude-shift keyed signals: **5**, 126-128
Analog-digital converter: **3**, 121-123
Analog-to-code converters: **3**, 49-52
Analog-to-digit conversion of repetitive signals: **11**, 87-88
Analysis of operating modes: **8**, 113-115
Analytical and numerical estimates of power: **11**, 135-137
Angle-measuring systems: **12**, 121-125
Angular coordinate: **4**, 86-90
Angular motion with periodic *a posteriori* probability density : **12**, 109-113
Anomalous errors: **3**, 69-73
Antenna array: **2**, 72-75
Antenna optimization: **11**, 47-54
Antenna pattern-shaping circuit: **7**, 74-78
Antennas: **3**, 16-30; **7**, 67-73
Antipodal focusing: **2**, 92-95
Aperture field distribution: **9**, 129-134
Apparatus failure: **4**, 129-130
Approximation of ideal integrators: **8**, 26-33
Arbitrary scanning law: **7**, 79-82
Archimedes spiral: **6**, 112-115
Astatic PLL system: **12**, 25-30
Asymmetrical cyclically varying modulation indices: **11**, 109-113
Atmospheric precipitation: **5**, 99-102
Atmospheric turbulence: **11**, 41-46
Attenuation: **5**, 18-23, 26-27, 28-29
Attenuation factor: **5**, 24-25
Autocompensators: **5**, 95-98
Automatic control: **7**, 128-134
Automatic frequency control: **3**, 60-61
Automatic plate modulation: **7**, 9-13
Availability coefficient: **9**, 1-10

Balanced dipole antenna: **5**, 44-46
Band-pass vacuum-tube oscillators: **10**, 67-72
Bandgap: **1**, 11-17
Bandpass filter-transformer: **10**, 14-20
Barycentric method: **5**, 30-36; **6**, 107-111
Binary data transmission: **1**, 90-95
Bipolar transistor: **1**, 60-63; **4**, 126-128
Bipolar transistors: **10**, 91-95
Blast wave: **2**, 11-16
Boolean functions: **3**, 94-98
Boxer-Taylor method: **1**, 96-103
Bragg diffraction: **3**, 139-140
Broadband oscillators: **7**, 4-8
Broadband signals: **7**, 118-127
Broadcast networks: **11**, 1-6, 7-15
Buffer memory: **10**, 61-66
Bulk integrated circuits: **7**, 14-22
Butterworth, Chebyshev, and Zolotarev-Cower approximations: **8**, 123-131

Cable communications lines: **2**, 11-16
Calculation of error probability: **12**, 135-139
Calculation of parameters of FET devices: **11**, 141-144
Carrier frequency measurement: **5**, 69-74
Carrier recovery: **4**, 13-16

Carrying capacity: **9**, 11-17
Catastrophic breakdown: **10**, 87-90
Category morphisms: **9**, 46-52
Cellular communications: **11**, 41-46
Cellular mobile communication system: **11**, 61-64
Cellular mobile communications: **5**, 9-12
Cellular mobile radio networks: **5**, 13-17
Cellular mobile radio systems: **5**, 1-8
Center of radiation: **5**, 30-36
Central limit theorem: **5**, 18-23; **7**, 53-55
Cepstrum coefficients: **9**, 22-27
Channel paralleling: **4**, 30-31
Channel splitter: **4**, 30-31
Channel with intersymbol interference: **8**, 52-54
Channel with Rayleigh fading: **12**, 135-139
Chaotic oscillations: **4**, 79-81
Charge resorption: **1**, 60-63
Charge-carrier plasma: **4**, 115-118
Chebyshev approximation: **10**, 14-20
Chebyshev criterion: **2**, 23-27
Chiral lightguide: **6**, 120-123
Chiral media: **6**, 120-123
Chokes: **10**, 132-135
Circuit and system synthesis: **8**, 42-45
Circuit symmetry: **4**, 138-139
Circuit-analysis algorithms: **1**, 55-59
Circular waveguides: **2**, 96-100
Classical sliding window algorithm: **8**, 79-82
Closed control system: **7**, 128-134
Code words: **9**, 18-21
Codec: **6**, 27-31
Coding: **2**, 76-78; **9**, 11-17
Coefficient of mutual induction: **9**, 28-31
Coherent and incoherent storage: **7**, 111-117
Coherent multiposition measuring systems: **7**, 118-127
Coherent sources: **12**, 74-80
Coherent summing: **3**, 139-140
Color signal interference: **5**, 52-60
Color television: **5**, 52-60; **10**, 1-6
Color television systems: **1**, 49-54
Combination frequencies: **1**, 132-135
Combinatorial optimization: **5**, 123-125
Combined filtering: **2**, 79-85
Combined matching: **10**, 136-140
Combined nonlinear filtering of Markov processes: **8**, 46-51
Combined protection of power supplies: **8**, 144-145
Communications cables: **9**, 28-31
Communications channels: **3**, 1-7, 108-111
Communications lines: **9**, 1-10
Communications systems: **6**, 24-26
Companding: **3**, 80-83
Complex exponent generator: **9**, 72-75
Complex images: **3**, 69-73
Complex signal processing: **6**, 50-63
Complex signals: **6**, 76-79
Complex signals pseudorandom sequence: **2**, 51-59
Complicated flight path: **11**, 55-60
Composite and random grade: **6**, 41-49
Composite nonlinear sequences: **6**, 76-79
Computer design of filters: **9**, 98-101
Computer modeling results: **8**, 113-115
Concentrated interference: **3**, 144-145
Conditions for minimizing noise factor: **11**, 82-86
Connectedness probability: **6**, 41-49
Contact impedance: **2**, 17-20
Continuous phase modulated signal: **3**, 53-55
Continuous phase modulation: **6**, 90-95
Continuous PLL systems: **12**, 31-35
Control-voltage supply: **12**, 140-141
Controllable delay circuits: **5**, 61-68
Controllable plane-layered media: **10**, 118-125
Controllable-gain amplifier: **6**, 133-134
Controlled generators: **7**, 41-43
Conversion procedure: **11**, 87-88
Converter: **11**, 132-134
Convolution sectioning method: **12**, 48-53
Coordination zone computation: **11**, 35-37
Correct-detection probability: **7**, 111-117; **9**, 135-138
Correlated interference: **2**, 79-85
Correlation feedback: **5**, 95-98
Correlation field: **2**, 119-124
Correlation function: **4**, 70-74
Correlation integral: **7**, 29-36
Correlation matrix: **4**, 82-85
Correlation matrix signal-to-noise ratio: **3**, 31-48
Correlation method: **10**, 141-143
Corrugated slotted line: **7**, 14-22
Covering density: **3**, 84-89
Cramer-Rao limit: **12**, 74-80
Cumulants: **9**, 46-52
Current distribution of surface beneath radiator: **8**, 100-103
Current switch: **1**, 22-27

Damage probability: **6**, 1-7
Data capacity in passive digital synthesizer: **11**, 65-68
Data processing: **7**, 14-22
Data transmission: **1**, 85-89; **10**, 126-128
Decameter radio communication systems: **6**, 67-70
Decentralized adaptive control: **11**, 22-28

Decision rules and their efficiency: **11**, 103-108
Decision statistics: **1**, 68-72
Decoder: **5**, 52-60
Decoding of linear block codes: **11**, 99-102
Decomposition: **1**, 1-5
Delay-line parameters that minimize size: **8**, 104-105
Demodulation based on a Kalman filter: **8**, 52-54
Demodulator: **7**, 26-28
Design of digital recursive filters: **8**, 123-131
Detection of noisy image contours: **12**, 59-65
Deterministic model: **10**, 67-72
Differential Taylor spectrum: **3**, 65-68
Diffraction efficiency: **2**, 119-124
Diffusely reflected radiation: **8**, 106-112
32-Digit nonlinear pseudorandom sequences: **10**, 115-117
Digital data transmission: **2**, 76-78; **5**, 61-68
Digital demodulator: **6**, 96-102
Digital filtering of radio signals: **11**, 93-98
Digital filters: **1**, 81-84, 104-107; **2**, 47-50; **3**, 90-93
Digital frequency discriminators: **1**, 64-67
Digital frequency-control loop: **12**, 18-24
Digital phase filters: **10**, 21-25
Digital processing: **2**, 31-35
Digital reception of radio signal: **12**, 54-58
Digital recursive filter synthesis methods: **10**, 73-82
Digital recursive filters: **1**, 96-103
Digital sequences: **3**, 94-98
Digital sound-broadcasting systems: **2**, 101-103
Dipole antenna: **4**, 26-29
Dipoles: **5**, 47-51, 107-109
Direct and indirect nonlinear filtering: **8**, 46-51
Direction finder: **10**, 103-106
Direction finders: **9**, 32-39
Directional antennas: **9**, 32-39
Directivity: **2**, 112-118; **5**, 103-106
Director antennas: **5**, 107-109
Discrete and continuous parameters: **11**, 93-98
Discrete convolution: **1**, 28-33
Discrete Fourier series: **7**, 64-66
Discrete integration synthesis methods: **10**, 73-82
Discrete Markov process: **10**, 40-45
Discrete multifrequency signals: **8**, 65-69
Discrete observation algorithms: **1**, 39-44
Discrete phasing: **5**, 103-106
Discrete store: **10**, 46-50
Discriminators: **7**, 29-36
Disjunctive normal form: **3**, 94-98
Distortion: **3**, 137-138
Distortions in broadcast transmitter: **11**, 76-81
Distributed targets: **9**, 46-52
Distributed-gain amplifiers: **4**, 138-139
Distribution density: **3**, 49-52
Diversity reception: **2**, 60-63
Division factor: **6**, 139-141
Doppler effect: **5**, 110-114
Doppler modulation: **7**, 97-103
Dynamic kinematic filtering method: **12**, 43-47
Dynamic programming: **2**, 104-107; **4**, 9-12
Dynistor: **10**, 100-102

Echo canceller: **2**, 1-7
Echo compensators: **4**, 32-35
Echo signals: **3**, 31-48; **4**, 1-8
Echo-signal suppression: **2**, 1-7
Effect of geometrical characteristics on directivity: **8**, 94-95
Effective width of target search zone: **8**, 17-20
Effects on energy efficiency of radio links: **11**, 109-113
EHF multibeam antenna: **7**, 74-78
Electrical echo: **4**, 32-35
Electrically controllable transparency: **5**, 118-122
Electroacoustic channel: **2**, 8-10
Electromagnetic compatibility: **2**, 108-111; **5**, 1-8; **11**, 29-34, 35-37, 118-124
Electromagnetic field structure: **5**, 115-117
Electromagnetic fields: **4**, 100-103
Electromagnetic-compatibility parameters: **2**, 112-118
Electronic circuits: **4**, 131-135
Electronic countermeasures: **8**, 17-20
Electronic frequency tuning: **10**, 91-95
Electronic systems: **7**, 83-88
Electronic warfare: **7**, 89-96
Element-by-element decision making: **9**, 102-106
Elevation errors: **10**, 103-106
Emitter-collector feedback: **10**, 83-86
Energy channel: **9**, 129-134
Energy characteristics of phase shifters: **11**, 72-75
Energy losses in digital processing: **12**, 54-58
Energy potential of cellular communication system: **11**, 61-64
Error probability: **1**, 90-95
Estimate of technical and economic efficiency: **6**, 67-70
Estimation of pulse repetition period: **8**, 55-60
Euler-Lagrange equations: **3**, 1-7
Excitation reliability: **1**, 139-142
Expansion of bandwidth: **8**, 119-122
Expansion of traditional radiosonde observations: **8**, 83-93
Explosions: **2**, 11-16

Extended target: **4**, 86-90
External parameters of 8-arm sector-waveguide bridge: **8**, 96-99

Fading: **2**, 68-71; **6**, 13-19
False-alarm probability: **1**, 68-72; **7**, 111-117; **10**, 107-110
Fan-shaped surface acoustic wave transducers: **9**, 98-101
Fast Fourier transform: **5**, 69-74; **7**, 64-66
Faster operating signal filtering algorithm: **8**, 79-82
Fault diagnosis in audio broadcasting: **4**, 140-141
Feedback: **4**, 36-41, 45-50; **6**, 133-134
FET self-excited oscillator: **3**, 56-59
Fiber lightguides: **6**, 120-123
Field topology: **7**, 26-28
Field-effect transistor: **4**, 131-135
Filter: **5**, 126-128
Filter functioning features: **6**, 64-66
Filter synthesis from analog filter prototype: **8**, 26-33
Filter-corrector: **3**, 1-7
Filtering algorithm: **12**, 43-47
Filtering algorithms with failure warning: **12**, 114-120
Filters with continuously adjustable AFC: **8**, 104-105
Filters with fan-shaped transducers: **9**, 98-101
Floquet waveguide: **2**, 96-100
Fluctuation spectrum of the errors: **11**, 145-146
FM demodulation: **6**, 96-102
Frequency: **11**, 29-34
Frequency allocation: **5**, 13-17; **11**, 22-28
Frequency band allocation: **11**, 7-15
Frequency band utilization: **11**, 16-21
Frequency converters: **12**, 31-35
Frequency correction method: **7**, 44-48
Frequency dependence of susceptances: **8**, 119-122
Frequency distortion: **7**, 29-36
Frequency modes of operation: **11**, 118-124
Frequency modulation: **3**, 80-83; **9**, 139-143
Frequency modulator: **9**, 80-82
Frequency multipliers: **1**, 73-78
Frequency resolution: **9**, 93-97
Frequency resolution of dispersion Fourier processor: **9**, 93-97
Frequency sharing: **11**, 35-37
Frequency stabilizers: **3**, 8-15
Frequency synthesizers: **1**, 64-67, 132-135; **3**, 8-15; **4**, 45-50; **6**, 139-141; **7**, 37-40
Frequency-band allocation: **11**, 1-6
Frequency-compact coding: **6**, 90-95
Frequency-hopping method: **9**, 102-106
Frequency-phase detector: **4**, 13-16
Frequency-phase lock automatic control systems: **12**, 18-24
Full-scale experiments: **8**, 37-41
Functional Volterra series: **7**, 49-52

Gain sensitivity: **7**, 44-48
Game-theory synthesis of signal structures: **8**, 65-69
Gaussian estimate of motion parameters: **12**, 98-101
Gaussian noise: **3**, 16-30; **5**, 92-94
Gaussian noise minimization: **5**, 84-88
Gaussian random field: **6**, 50-63
General bilinear transformation procedure: **8**, 123-131
General hierarchical motion-parameter estimation: **12**, 102-108
Generator circuits: **1**, 73-78
Geometrical optics: **6**, 107-111
Geostationary orbit: **4**, 17-21
Ghosts: **4**, 1-8
Global asymptotic stability: **3**, 8-15
Graphical description of frequency conversion: **8**, 132-134
Gunn diode: **9**, 76-79

Half-wave voltage converter: **4**, 36-41
Harmonic oscillations: **9**, 72-75
Helical antenna: **2**, 134-136
Helical line: **3**, 112-114
Hermetically sealed relays: **9**, 40-45
Heterodynes: **6**, 20-23
High-pass pi-section filters: **12**, 140-141
High-Q filtering: **2**, 28-30
Hilbert converter: **12**, 66-68
Hilbert transformation: **10**, 21-25
Hybrid method: **12**, 74-80

Identification of directions: **12**, 121-125
Identification of parameters of medium: **8**, 106-112
Image-forming radiometric correlation-extremum systems: **10**, 35-39
Immersion liquid: **7**, 1-3
IMPATT diode operating instability: **8**, 116-118
Impedance antennas: **4**, 96-99
Impedance parameters: **12**, 11-13
Improved overload protection: **8**, 113-115
Impulse interference: **10**, 51-55
Impulse microwave interference: **10**, 87-90
Incoherent storage: **7**, 97-103
Information blocks: **9**, 18-21
Information index: **9**, 22-27

Information transmission channels: **6**, 24-26
Instant of first observability: **12**, 98-101
Integral lattice: **3**, 84-89
Integrated circuits: **9**, 11-17
Integrodifference equations: **6**, 32-40
Integrodifferential equations: **4**, 91-95; **6**, 32-40
Interaction at harmonics: **8**, 37-41
Interference: **1**, 85-89, 132-135; **2**, 64-67; **3**, 16-30, 99-104; **9**, 111-118; **10**, 51-55, 111-114
Interference filtering: **12**, 25-30
Interference immunity: **11**, 114-117; **12**, 130-134
Interference immunity characteristics: **12**, 54-58
Interference immunity of signal reception in white noise: **11**, 109-113
Interference sources: **4**, 82-85
Interference with aircraft navigational equipment: **5**, 9-12
Interference-suppressing filters: **10**, 132-135
Interference-suppression: **8**, 144-145
Intermodulation dynamic range: **9**, 83-87
Intermodulation oscillation frequencies: **8**, 132-134
Intersymbol interference: **5**, 92-94; **9**, 102-106
Ionosphere: **1**, 123-125, 126-128
Ionosphere radio-wave propagation: **3**, 108-111
Ionospheric diagnostics: **8**, 83-93
Ionospheric radio waveguides: **2**, 92-95
Ionospheric signal: **5**, 110-114
IP-parameters: **9**, 83-87
Itakura-Saito criterion: **9**, 22-27

Jamming: **7**, 89-96; **10**, 35-39
Jitter: **6**, 20-23
Johnson distribution: **2**, 108-111
Joint ventures in Russia: **12**, 14-17

Laser: **9**, 135-138
Laser radar system: **8**, 21-25
Laser radiation: **3**, 139-140
Laser scanning viewing system: **7**, 79-82
Laser-controlled rotating microwave waveguide junction: **11**, 129-131
Lattice filters: **4**, 82-85
Layered medium: **6**, 112-115
Layered randomly inhomogeneous medium: **8**, 106-112
LCR measurements: **12**, 11-13
LCR parameters of passive transducers: **12**, 11-13
Leaking current wave: **10**, 129-131
LFM signals: **6**, 83-84
Light guides: **2**, 125-128
Light-emitting diodes: **4**, 51-55
Lightguide: **7**, 1-3
Likelihood function: **9**, 53-60
Likelihood ratio: **9**, 135-138
Likelihood-ratio functional: **4**, 119-125
Limit cycles: **12**, 36-42
Limiting superresolution characteristics: **12**, 74-80
Linear electric circuits: **2**, 137-139
Linear frequency modulation: **3**, 137-138
Linear networks: **6**, 1-7
Linear recurrent sequences: **9**, 119-125
Linear-prediction method: **9**, 22-27
Load mismatch: **7**, 4-8
Loaded ladder structure: **5**, 37-43
Local feedback loop: **7**, 44-48
Log-periodic antennas: **9**, 32-39
Logarithmic amplifiers: **6**, 131-132
Logic elements: **6**, 76-79
Loss of estimation accuracy: **8**, 55-60
Low-contrast distributed radar targets: **10**, 26-34
Low-frequency predistortions: **10**, 1-6
Low-noise microwave amplifiers: **10**, 83-86
Low-noise transistor amplifier: **10**, 96-99
Low-noise transistor microwave amplifiers: **10**, 136-140
Low-noise transistor microwave reflex amplifier: **11**, 82-86
Low-pass filter: **4**, 136-137
Low-pass, high-pass, band-pass and rejection filters: **8**, 123-131
Low-power divider: **6**, 139-141

m-ary orthogonal signals: **1**, 85-89
M-sequences: **5**, 89-91
M-sequences: **10**, 115-117
Magnetic conductor: **10**, 132-135
Maneuvering inconspicuous targets: **6**, 64-66
Markov chain: **7**, 56-63
Markov optimal estimation theory: **6**, 50-63
Markov processes: **9**, 119-125
Markov sequences: **2**, 79-85
Markov signal model: **9**, 111-118
Markov theory of filtering: **2**, 31-35
Matched filter: **2**, 51-59; **6**, 83-84
Matching: **7**, 41-43
Mathematical expectation: **1**, 68-72
Mathematical relations for analyzing stability: **8**, 141-143
Mathematical simulation results: **8**, 37-41
Matrix algorithm for discrete approximation: **8**, 26-33
Matrix crystals: **9**, 11-17
Matrix multiplier: **5**, 118-122

Maximum information effect: **6**, 85-89
Maximum usable frequency: **1**, 123-125
Maximum-entropy method: **9**, 22-27
Maximum-likelihood criterion: **5**, 92-94
Maximum-likelihood estimate: **3**, 69-73; **4**, 86-90
Maximum-likelihood methods: **4**, 119-125
Maximum-likelihood receiver: **6**, 90-95
Mean error probability: **5**, 92-94
Medved-Truxal method: **1**, 96-103
Memory elements array: **6**, 76-79
Meteor communications link: **10**, 126-128
Meteor showers: **10**, 126-128
Meteorological attenuation factor: **1**, 111-115
Meteorological interference: **1**, 111-115
Meter-band radio waves: **2**, 101-103
Method of doubling spectrum analyzer bandwidth: **6**, 128-130
Method of least weighted squares: **2**, 8-10
Method of moments: **10**, 40-45
Method of reducing parasitic harmonic radiation: **11**, 69-71
Microprocessors: **6**, 8-12
Microwave amplifier: **6**, 131-132
Microwave attenuators: **1**, 79-80
Microwave bulk integrated circuit: **7**, 26-28
Microwave detector-mixer module: **8**, 113-115
Microwave field-effect transistors: **1**, 136-138
Microwave IC's: **1**, 55-59
Microwave modulator: **4**, 115-118
Microwave self-excited oscillator: **9**, 76-79
Microwave subcarriers: **6**, 116-119
Millimeter wave radio: **11**, 41-46
Minimax interference filtering problems: **12**, 109-113
Minimization of radio noise: **11**, 41-46
Minimum data capacity without signal degradation: **11**, 65-68
Mirror antennas: **2**, 86-91; **5**, 30-36
Mixed Markov process: **7**, 89-96
Mobile antennas: **2**, 64-67
Mobile communications: **11**, 1-6, 7-15
Mobile radio communications: **2**, 108-111
Model illustrating bridge properties: **8**, 96-99
Modeling of propagation paths: **11**, 38-40
Modeling results: **11**, 99-102
Moment function: **4**, 63-69
Monopulse radar signals: **9**, 53-60
Monopulse satellite automatic tracking systems: **11**, 132-134
Monte Carlo model: **8**, 106-112
Motion parameters of groups of moving objects: **12**, 102-108
Moving target detection: **5**, 75-77
Multichannel measurement systems: **1**, 39-44
Multicriterial optimization: **1**, 34-38
Multifrequency linear-frequency-modulated signals: **12**, 126-129
Multifrequency radar: **7**, 135-141
Multifrequency signals: **2**, 68-71, 101-103
Multilayer meander line polarizers: **11**, 125-128
Multilayered earth: **4**, 100-103
Multimodulus arithmetic: **1**, 28-33
Multipath propagation: **2**, 101-103; **9**, 102-106
Multipath propagation: **6**, 13-19
Multipath radio signals: **7**, 53-55
Multipath signal characteristic function: **7**, 53-55
Multiple utilization of some frequency: **11**, 16-21
Multiple-input nonlinear radio devices: **7**, 49-52
Multiplexers: **4**, 56-62
Multiplexing noninertial sections of filters: **4**, 136-137
Multiplicative criteria: **2**, 36-38
Multiplicative noise: **9**, 119-125
Multipliers: **3**, 115-120
Multiposition observation: **3**, 141-143
Multiposition signals: **7**, 56-63
Multistage optimization procedure: **9**, 67-71
Multiterminal networks: **2**, 43-46
Multivariate Maclaurin series: **7**, 49-52
Mutual interference: **1**, 90-95

n-dimensional moment: **3**, 49-52
Narrow-band interference: **2**, 51-59
Narrow-band signals in matched-filter systems: **8**, 135-138
Navigation systems: **12**, 114-120
Negative capacitance: **10**, 100-102
Negative differential resistance: **5**, 129-134; **10**, 100-102
Neural nets: **4**, 109-114
Nodes: **6**, 1-7
Noise: **3**, 1-7, 144-145; **6**, 20-23
Noise factor: **10**, 83-86, 136-140
Noise immunity: **1**, 6-10, 18-21, 85-89, 90-95; **2**, 51-59, 60-63, 68-71; **3**, 53-55, 80-83; **9**, 102-106, 107-110
Noise protection: **3**, 99-104
Noise reduction in a multicomponent signal: **5**, 78-83
Noise temperature: **10**, 96-99
Noisy impulse interference: **10**, 107-110
Noisy radiation: **4**, 82-85
Nomograms: **6**, 135-138
Nonambiguity range: **9**, 88-92

Nonlinear amplifier: **5**, 126-128
Nonlinear components: **3**, 115-120
Nonlinear distortion: **2**, 39-42; **6**, 96-102
Nonlinear filtering: **9**, 119-125
Nonlinear filtering of Markov processes: **12**, 43-47
Nonlinear phase variation: **12**, 54-58
Nonlinear pulsed circuits: **6**, 71-75
Nonlinear systems: **7**, 128-134
Nonlinear two-ports: **9**, 83-87
Nonlinearity coefficient: **1**, 22-27
Nonlinearly frequency-modulated signals: **4**, 70-74
Nonrecursive digital correctors: **2**, 23-27
Nonuniform helix: **2**, 134-136
Number-theoretic transformations: **1**, 28-33
Numerical integration method: **7**, 49-52
Nyquist frequency: **1**, 116-122
Nyquist slopes: **4**, 1-8

One- and four-layer polarizers: **11**, 125-128
Operation under jamming conditions: **8**, 21-25
Operator short-circuit admittance: **2**, 43-46
Optical cables: **5**, 24-25, 26-27, 28-29
Optical computers: **2**, 129-133
Optical data processing: **4**, 109-114
Optical fiber communications lines: **9**, 1-10
Optical fibers: **5**, 18-23, 24-25; **6**, 116-119; **9**, 11-17
Optical image: **4**, 119-125; **6**, 85-89
Optical radiation propagation: **8**, 106-112
Optical switch: **7**, 1-3
Optical-fiber sensors: **2**, 125-128
Optimal detectors: **3**, 16-30
Optimal excitation zone: **2**, 86-91
Optimal frequency distribution: **4**, 9-12
Optimal linear reception: **3**, 1-7
Optimal observation control algorithms: **1**, 39-44
Optimal processing: **3**, 31-48
Optimality: **2**, 36-38
Optimization of complex technical systems: **9**, 67-71
Optimization of log-periodic radiator emission: **8**, 100-103
Optimization of model energy parameters: **10**, 67-72
Optimization of radar signal processing: **12**, 81-86
Optimum and quasioptimum target selection: **7**, 104-110
Optimum detection algorithms for different contours: **12**, 59-65
Optimum minimax estimate of angular motion: **12**, 109-113
Optimum radiation divergence angle: **8**, 21-25
Optimum radiation pattern: **7**, 74-78
Optimum radio navigation equipment performance: **12**, 114-120
Optimum weighting factors: **12**, 66-68
Order of nonlinearity: **3**, 94-98
Orthogonal cyclic codes: **3**, 74-79
Orthogonal system of basis functions: **11**, 125-128
Output vector modulus of contour matched filter: **12**, 59-65
Overhead wire: **4**, 100-103
Overvoltage mode: **7**, 9-13
Owen function: **1**, 18-21

p-n junctions: **1**, 11-17
p-n-p-n-structure: **5**, 129-134
Packing density: **3**, 84-89
Paired targets: **9**, 53-60
Parallel plate modulation: **7**, 9-13
Parameter values for given harmonic coefficients: **11**, 141-144
Parametric and nonparametric uncertainty: **11**, 103-108
Parasitic amplitude modulation: **9**, 80-82
Parasitic cyclic motions: **12**, 18-24
Parasitic harmonic radiation: **11**, 69-71
Pareto-optimum versions: **2**, 36-38
Partial beams: **2**, 86-91
Partial coherent synthetic-aperture radars: **8**, 74-78
Partial differential equations: **2**, 129-133
Particular functional tasks: **7**, 83-88
Passive digital frequency synthesizer: **5**, 61-68
Passive interference: **2**, 72-75
Passive transducers: **12**, 11-13
Pattern-forming network: **2**, 112-118
Performance of alternative power supplies: **11**, 89-92
Periodic autocorrelation function: **10**, 115-117
Periodic correlation function: **3**, 74-79
Periodic modulation signal: **5**, 37-43
Periodic signals: **7**, 64-66
Periodically loaded wire: **10**, 129-131
Phase antenna array: **9**, 83-87
Phase detector: **4**, 13-16
Phase diagram: **6**, 90-95
Phase difference between sources: **12**, 74-80
Phase directivity pattern of biconical radiator: **8**, 94-95
Phase error: **2**, 86-91
Phase noise: **3**, 127-131; **4**, 45-50
Phase shifter analysis using energy diagram: **11**, 72-75
Phase-delayed feedback amplifiers: **7**, 44-48

Phase-locked loop: **3**, 8-15; **4**, 45-50; **12**, 36-42
Phase-locked loop system: **6**, 32-40
Phase-shift keyed signals: **2**, 51-59; **5**, 126-128; **6**, 80-82
Phase-shift keying: **2**, 76-78
Phased antenna array: **5**, 99-102, 103-106; **7**, 111-117
Phased antenna arrays: **2**, 96-100
Phasing error: **3**, 62-64
Phasing system: **3**, 62-64
Photodetector: **1**, 129-131
Piecewise-linear differential equations: **1**, 73-78
Pin-diodes: **1**, 79-80
Planar waveguide array: **6**, 103-106
Planning of cellular networks: **5**, 13-17
Poisson flow: **10**, 46-50
Poisson stream of events: **10**, 40-45
Polarization degeneracy: **6**, 120-123
Polarization ellipse: **10**, 129-131
Polarization scattering matrix: **9**, 61-66
Polychromic color display: **7**, 135-141
Polynomial transformations: **1**, 28-33
Power adder: **4**, 30-31
Power analysis of discrete phase shifters: **11**, 72-75
Power divider: **4**, 30-31
Power emission into ionospheric plasma: **11**, 135-137
Power loss reduction: **4**, 30-31
Power supplies: **4**, 42-44; **10**, 7-13
Precipitation intensity: **7**, 67-73
Precision potentiometers: **3**, 115-120
Prediction coefficients: **6**, 27-31
Predistortion: **2**, 39-42; **10**, 1-6
Prescalar: **6**, 139-141
Prevention of interference: **11**, 38-40
Principle of superposition: **3**, 53-55
Printed spiral radiator: **6**, 112-115
Priority vector: **6**, 8-12
Probability characteristics: **4**, 63-69
Probability characteristics of rule: **8**, 70-73
Probability distribution: **5**, 110-114
Probability of failure to serve subscribers: **11**, 61-64
Processing of field measurements in Fresnel zone: **8**, 61-64
Propagation-medium simulator: **6**, 13-19
Proportional-integral filter: **3**, 60-61
Protection circuits: **9**, 40-45
Pseudoenvelope: **4**, 63-69
Pseudorandom sequences: **7**, 56-63
PSK signals: **5**, 69-74, 84-88
Pull-in range: **12**, 36-42
Pulse PLL system: **12**, 25-30
Pulse response: **1**, 104-107
Pulse-width modulation: **8**, 11-16
Pulsed interference and noise: **8**, 70-73
Pulsed modulation of semiconductor laser current: **11**, 138-140
Pulsed optical phase modulation of semiconductor laser: **11**, 138-140
Pulsed optical signals light-emitting matrix: **5**, 118-122
Pulsed phase-locked systems: **3**, 8-15
Pulsed stabilizers: **8**, 11-16
Push-pull amplifier: **4**, 138-139

Quadrature amplitude modulation: **6**, 20-23
Quadrature amplitude-phase shift keying: **1**, 18-21
Quadrature quantization: **8**, 135-138
Quality factor: **4**, 104-108
Quantization error: **2**, 8-10; **3**, 49-52
Quartz oscillators: **1**, 139-142; **3**, 127-131; **9**, 139-143
Quartz rejection filter: **3**, 127-131
Quartz resonator: **1**, 139-142
Quartz resonators resistance transformer: **3**, 124-126
Quartz self-excited oscillators: **3**, 124-126
Quasi-optimal receiver: **2**, 79-85
Quasiorthogonal signals: **1**, 90-95
Queuing system: **10**, 56-60, 61-66

R-matrices: **3**, 115-120
Radar: **9**, 135-138
Radar detection of oil films on water: **12**, 81-86
Radar image: **4**, 75-78
Radar measurements of sea surface wave spectrum: **12**, 91-97
Radar scattering characteristics of objects: **8**, 61-64
Radar sets: **3**, 141-143
Radar systems: **3**, 16-30; **7**, 89-96, 111-117
Radar target detection algorithm: **10**, 26-34
Radar targets: **1**, 45-48
Radar techniques: **1**, 108-110
Radar velocity portrait: **7**, 97-103
Radar-transparent sheath materials: **7**, 67-73
Radiation pattern: **1**, 116-122; **2**, 72-75; **3**, 99-104; **4**, 22-25, 75-78; **5**, 44-46, 115-117; **6**, 103-106, 107-111
Radiation patterns: **2**, 112-118; **5**, 47-51
Radio and television antennas: **4**, 22-25
Radio hologram: **4**, 75-78
Radio links: **2**, 104-107; **4**, 9-12
Radio navigation: **5**, 1-8
Radio navigation system: **6**, 50-63

Radio range-finder: **3**, 137-138
Radio rangefinder: **2**, 31-35
Radio signal reflection from atmospheric interfaces: **1**, 108-110
Radio systems: **2**, 36-38
Radio transmitters: **7**, 4-8
Radio-electronic apparatus: **4**, 129-130
Radio-frequency allocation: **5**, 9-12
Radio-receiving channels: **3**, 65-68
Radio-wave propagation: **1**, 126-128
Radio-wave reflection: **1**, 123-125
Radioaltimeters: **9**, 88-92
Radiowave propagation: **1**, 111-115
Radomes: **4**, 104-108
Railroad transport communications systems: **10**, 51-55
Rain: **7**, 67-73
Random process: **4**, 63-69
Range spectrum of re-reflection from surface: **12**, 87-90
Ranging accuracy: **3**, 137-138
Ratio of coherent and noncoherent storage: **8**, 74-78
Rayleigh fading: **9**, 102-106
RC integrating circuit: **3**, 121-123
Reactance plane: **4**, 96-99
Real time operation: **6**, 8-12
Real-time automatic testing system: **8**, 70-73
Receiver side-band frequencies: **8**, 132-134
Receiving filter: **10**, 111-114
Reception of binary signals: **8**, 52-54
Reception of *m*-ary orthogonal signals: **12**, 135-139
Recirculator with shifting heterodyne: **12**, 126-129
Rectangular waveguide: **9**, 126-128
Rectifier circuit: **4**, 42-44
Recursive digital filters: **2**, 28-30
Reed-Solomon codes: **10**, 126-128
Reference voltage sources: **1**, 11-17
Reflector antennas: **1**, 116-122; **6**, 107-111
Refractive index: **7**, 1-3; **8**, 1-10
Regenerator: **6**, 80-82
Regions of loss of radio signals: **1**, 108-110
Regions with increased background variance: **10**, 26-34
Regression models: **3**, 90-93
Regulation error: **8**, 11-16
Regulation of communication enterprises: **12**, 14-17
Reliability: **9**, 1-10
Reradiation antennas: **4**, 91-95
Resonantly coupled oscillators: **8**, 37-41
Results of numerical modeling for LFM signals: **8**, 135-138
Ribbed dielectric lines: **7**, 14-22
Ring network: **6**, 1-7
Rotating waveguide channel: **11**, 129-131
Round-the-world signals: **2**, 92-95
Rounding error: **2**, 28-30

S-shaped current-voltage characteristic: **10**, 100-102
S-type current-voltage characteristic: **5**, 129-134
S/N ratio: **5**, 9-12
S/N ratio in microwave circuits: **1**, 55-59
Sampling: **3**, 84-89
Sampling frequency: **1**, 104-107
Satellite broadcasting: **5**, 30-36
Satellite television antenna: **4**, 17-21
Sawtooth generators: **1**, 22-27
Scanning curves: **6**, 107-111
Scattering characteristics: **1**, 45-48
Scattering functions: **9**, 46-52
Scattering indicatrix: **9**, 61-66
Scattering parameters: **3**, 56-59
Schottky-barrier field-effect transistors: **10**, 87-90
Scott and Hetschel codes: **9**, 107-110
Screened surface-wave lines: **7**, 14-22
Screening attenuation: **2**, 17-20
Search for light-pulse sources: **6**, 124-127
Secondary power supply: **4**, 36-41
Secondary spectral component frequencies: **8**, 132-134
Selective removal of electrodes: **9**, 98-101
Selector of low-velocity targets: **7**, 104-110
Self-complimentary antennas: **5**, 47-51
Self-excited oscillator: **4**, 126-128
Self-excited oscillatory systems: **10**, 91-95
Self-orthogonal vector codes: **9**, 107-110
Semiconductor diode: **1**, 73-78
Semiconductor injection laser: **2**, 125-128
Semiconductor switch: **4**, 42-44
Semiconductor waveguide: **4**, 115-118
Sensitivity: **10**, 96-99
Separation of frequency users: **11**, 29-34
Shared frequencies: **11**, 38-40
Shared frequency use: **11**, 22-28
Sharing of frequency bands: **11**, 29-34
Shift register: **5**, 89-91
Short-wave communications: **1**, 126-128
Shortwave radio: **11**, 47-54
Shortwave signal: **5**, 110-114
Signal attenuation: **5**, 1-8
Signal coding: **6**, 27-31
Signal detection: **8**, 70-73
Signal detection rule: **8**, 70-73

Signal detection under uncertainty conditions: **11**, 103-108
Signal detector efficiency: **5**, 84-88
Signal envelope: **5**, 75-77
Signal function: **3**, 69-73
Signal parameter estimation: **5**, 78-83
Signal power distribution function: **5**, 78-83
Signal power spectral density: **12**, 130-134
Signal predistortion: **1**, 6-10
Signal processing: **1**, 81-84
Signal processing and shaping in radio monitoring: **10**, 141-143
Signal transformation to complex number field: **12**, 48-53
Signal-detection theory: **3**, 16-30
Signal-level monitoring in broadcasting: **4**, 140-141
Signal-position fixers: **10**, 111-114
Signal-source admittance: **10**, 96-99
Signal to interference-plus-noise ratio: **2**, 104-107
Signal-to-noise ratio: **1**, 129-131; **2**, 68-71, 119-124; **4**, 86-90, 119-125; **7**, 111-117; **12**, 74-80
Signal/interference ratio criterion: **8**, 34-36
Simulation of decameter systems: **6**, 67-70
Single-line queuing system: **10**, 56-60
Single-sideband signal: **2**, 47-50; **3**, 80-83
Single-stage amplifier: **2**, 137-139
Slot radiator: **5**, 115-117
Slotted array: **9**, 126-128
Smoothing effectiveness: **3**, 121-123
Soft decoding procedure algorithm: **11**, 99-102
Solution of convolution integral: **10**, 73-82
Solution of Zolotarev polynomial problem: **8**, 42-45
Sound broadcasting: **6**, 27-31
Space-time holography: **4**, 109-114
Space-time signal: **3**, 141-143
Space-time signal processing: **2**, 64-67; **5**, 75-77; **7**, 118-127; **9**, 111-118
Sparse matrix techniques: **1**, 55-59
Spatial energy spectrum of sea waves: **12**, 91-97
Spatial-frequency filtering: **2**, 129-133
Spatially correlated interference: **3**, 31-48
Spectral analysis of signals in Galois field: **12**, 48-53
Spectral density: **7**, 56-63
Speech intelligibility: **2**, 8-10
Spline functions: **1**, 136-138
Spline-approximation method: **12**, 43-47
Splines: **10**, 51-55
Sporadic E-layer: **3**, 108-111
Spread-spectrum signal: **7**, 29-36
Spread-spectrum signals: **10**, 115-117
Square-law detection: **10**, 107-110
Stability of autodyne asynchronous microwave systems: **8**, 141-143
Stabilitron: **10**, 7-13
Stable distributions: **7**, 53-55
Standby devices: **10**, 56-60
Star networks: **6**, 1-7
Statistical image transforms: **6**, 85-89
Statistical normalization: **5**, 18-23
Statistical properties of signal fluctuations: **5**, 1-8
Statistical signal analysis: **1**, 111-115
Statistical transmission systems: **9**, 18-21
Steady-state linear discrete system: **12**, 98-101
Steady-state signals and interference: **8**, 34-36
Step-by-step sliding window (SSW) filter algorithm: **8**, 79-82
Stepped random sequences: **7**, 56-63
Stereocamera: **4**, 51-55
Stereopairs: **4**, 51-55
Stereotelevision: **4**, 51-55
Stimulated photon echo: **4**, 109-114
Stochastic oscillations: **4**, 79-81
Stochastic signal detection: **9**, 111-118
Stochastic signals: **3**, 31-48
Stress tensors: **8**, 1-10
Strip lines: **1**, 79-80
Stripline: **7**, 26-28
Stripline feeder: **3**, 105-107
Structural reliability: **6**, 41-49
Sufficient statistic: **12**, 59-65
Sum-difference converters of 5-mm band waves: **11**, 132-134
Super-resolution algorithm: **1**, 45-48
Superposition of tracer noise signal: **1**, 81-84
Superresolution criterion: **12**, 74-80
Supply currents: **8**, 116-118
Surface acoustic wave delay lines: **6**, 83-84
Surface admittance: **4**, 96-99
Surface effects on log-periodic radiator emission: **8**, 100-103
Surface reflection function: **7**, 97-103
Surface relief: **6**, 50-63
Surface wave: **3**, 112-114
Switch ARC-filters: **3**, 115-120
Switchable-capacitor filters: **4**, 136-137
Switched power amplifier: **10**, 14-20
Switching circuits: **6**, 8-12
Switching junctions: **1**, 1-5
Switching units: **10**, 61-66
Symmetry groups: **3**, 84-89
Synthesis of masking jamming: **10**, 35-39
Synthesized aperture: **4**, 75-78

Synthetic-aperture forward-looking radar: **11**, 55-60
Synthetic-aperture radar: **8**, 17-20
Synthetic-aperture radar systems: **7**, 97-103
System efficiency criterion: **11**, 61-64
Systems approach to electronic equipment synthesis: **7**, 83-88

Target detection in jamming background: **8**, 74-78
Target search zone smaller than scanning zone: **8**, 17-20
Target tracking filters: **6**, 64-66
Telephone exchanges: **1**, 1-5
Telephone networks: **2**, 1-7
Television picture quality: **1**, 49-54; **5**, 52-60
Television receivers: **4**, 1-8
Television signals: **1**, 49-54; **2**, 39-42
Temperature instability: **1**, 11-17
Temporal information processing algorithms: **16**, 124-127
Temporal weighting: **7**, 104-110
Tensor Green's functions: **10**, 118-125
Theory of equivalent transmission lines: **10**, 118-125
Theory of periodic structures: **10**, 118-125
Threshold elements: **4**, 56-62
Thyristor: **10**, 7-13
Thyristor short-circuits: **9**, 40-45
Time multiplexing: **11**, 16-21
Time parameters of bandpass filters: **12**, 1-10
Time parameters of low-pass filters: **12**, 1-10
Tone frequency channel: **2**, 23-27
Tone-frequency channels: **4**, 32-35
TOPEX orbital radioaltimeter: **9**, 88-92
Topological model: **7**, 23-25
Topological switch: **7**, 26-28
Total phase reconstruction from discrete phase readings: **11**, 114-117
Trajectory information: **11**, 145-146
Transfer constant: **6**, 133-134
Transformerless push-pull stages: **6**, 135-138
Transient characteristics of radio systems: **12**, 1-10
Transients control in filter: **1**, 81-84
Transients in AFC-equipped scanners: **1**, 64-67
Transients in switching: **1**, 60-63
Transistor circuits: **7**, 23-25
Transistor self-excited oscillators: **4**, 79-81
Transition probability matrices: **7**, 56-63
Transmission systems: **6**, 116-119
Transmitter parameters: **12**, 130-134
Transmitters: **7**, 9-13
Triads: **7**, 37-40
Troposphere radio wave propagation: **1**, 111-115
Truth table: **3**, 94-98
Tunable active filters: **3**, 115-120
Turnstile radiator: **3**, 105-107
TV reception: **5**, 30-36
Two-conductor lines: **5**, 44-46
Two-layer fiber lightguides: **8**, 1-10
Two-pole communications network: **6**, 41-49
Two-step estimation algorithm: **8**, 46-51

UHF oscillator: **10**, 91-95
Umbrella reflector: **6**, 107-111
Uncertainty function: **9**, 46-52
Uncorrelated interference: **3**, 31-48
Unitary rotations: **12**, 69-73
Unknown pulse amplitudes: **8**, 55-60
Unpremeditated interference sources: **11**, 118-124
Unresolved targets: **9**, 53-60
Unsteady processes: **4**, 131-135
Use of optrons in power circuits: **8**, 139-140

Value function: **5**, 123-125
Varactor: **4**, 126-128
Varactors: **10**, 91-95
Variable ballast, load and signal source: **8**, 119-122
Variable impedance: **5**, 37-43
Vector optimality criterion: **9**, 67-71
Vector optimality principle: **1**, 34-38
Vector outer product: **5**, 118-122
Velocity portrait of sea surface: **7**, 97-103
Voltage switch: **1**, 22-27
Voltage-controlled voltage source: **7**, 23-25
Volterra functional series: **3**, 65-68
Voron polyhedra: **3**, 84-89

Walsh functions: **6**, 71-75
Wave equation: **9**, 129-134
Waveguide iris: **9**, 126-128
Weighting of fan-shaped transducers: **9**, 98-101
Weighting vector: **5**, 95-98; **7**, 104-110
Wide-band microwave diode switch: **12**, 140-141
Wide-band power amplifiers: **11**, 69-71
Wide-band quadrature power divider: **8**, 119-122
Wide-band short-wave transmitters: **10**, 67-72
Wiener estimation algorithm: **3**, 90-93
Wilcockson detector: **1**, 68-72

Z-transform method: **1**, 96-103
Z-transformation: **3**, 74-79